

इंटरनेट

मानक

Disclosure to Promote the Right To Information

Whereas the Parliament of India has set out to provide a practical regime of right to information for citizens to secure access to information under the control of public authorities, in order to promote transparency and accountability in the working of every public authority, and whereas the attached publication of the Bureau of Indian Standards is of particular interest to the public, particularly disadvantaged communities and those engaged in the pursuit of education and knowledge, the attached public safety standard is made available to promote the timely dissemination of this information in an accurate manner to the public.

“जानने का अधिकार, जीने का अधिकार”

Mazdoor Kisan Shakti Sangathan

“The Right to Information, The Right to Live”

“पुराने को छोड़ नये के तरफ”

Jawaharlal Nehru

“Step Out From the Old to the New”

IS 8393 (1977): Roll Seal Pilferproof Closures [MTD 32: Metal Containers]



“ज्ञान से एक नये भारत का निर्माण”

Satyanarayan Gangaram Pitroda

“Invent a New India Using Knowledge”



“ज्ञान एक ऐसा खजाना है जो कभी चुराया नहीं जा सकता है”

Bhartrhari—Nitiśatakam

“Knowledge is such a treasure which cannot be stolen”

BLANK PAGE



IS : 8393 - 1977
(Reaffirmed 1995)

Indian Standard

SPECIFICATION FOR ROLL SEAL PILFERPROOF CLOSURES

(Third Reprint APRIL 1998)

UDC 683.533-12

© Copyright 1977

BUREAU OF INDIAN STANDARDS
MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG
NEW DELHI 110002

Indian Standard

SPECIFICATION FOR ROLL SEAL PILFERPROOF CLOSURES

Metal Containers Sectional Committee, MCPD 12

Chairman

SHRI L. SIKAND

Representing

The Metal Box Company of India Ltd, Calcutta

Members

SHRI J. K. KHOSLA (<i>Alternate to</i> Shri L. Sikand)	
SHRI V. P. AGARWAL	Hindustan Steel Limited, Rourkela
SHRI P. B. RAO (<i>Alternate</i>)	
SHRI B. R. AJMANI	Hindustan Petroleum Corporation Ltd, Bombay
SHRI K. SUNDARAM (<i>Alternate</i>)	
SHRI P. R. BHAGWAT	Ministry of Railways (Railway Board)
SHRI S. CHOWDHURY	I. C. I. (India) Pvt Ltd, Calcutta
SHRI B. KUMAR (<i>Alternate</i>)	
SHRI M. L. DAY	M. L. Day and Company, Calcutta
SHRI J. N. DEY (<i>Alternate</i>)	
SHRI V. V. GHOTGE	Balmer Lawrie & Co Ltd, Bombay
SHRI A. P. JOSEPH (<i>Alternate</i>)	
SHRI P. K. GUPTA	Containers and Closures Limited, Calcutta
SHRI A. K. BASU (<i>Alternate</i>)	
DR S. V. GUPTA	Directorate of Weights & Measures (Ministry of Industry & Civil Supplies)
SHRI SAMIUL HAQUE (<i>Alternate</i>)	
SHRI R. C. JHINGAN	Indian Oil Corporation Ltd, Bombay
SHRI M. A. MATHEW (<i>Alternate</i>)	
SHRI G. S. KADDET	Poysha Industrial Company Limited, Bombay
SHRI S. CHATTERJEE (<i>Alternate</i>)	
SHRI P. D. KATRAK	Zenith Tin Works Ltd, Bombay
SHRI A. R. A. KRISHNAN	Ministry of Defence (DGI)
MAJ S. K. MISRA (<i>Alternate</i>)	
SHRI S. LAKSHMIKANTHAN	Export Inspection Council (Ministry of Commerce)
SHRI P. K. DAS (<i>Alternate</i>)	
SHRI N. C. MAGOTRA	The Tinplate Company of India Ltd, Calcutta
SHRI P. K. BANERJEE (<i>Alternate</i>)	

(Continued on page 2)

© Copyright 1977

BUREAU OF INDIAN STANDARDS

This publication is protected under the *Indian Copyright Act* (XIV of 1957) and reproduction in whole or in part by any means except with written permission of the publisher shall be deemed to be an infringement of copyright under the said Act.

(Continued from page 1)

<i>Members</i>	<i>Representing</i>
SHRI A. N. MUKHERJEE	Directorate General of Technical Development, New Delhi
SHRI T. SUBRAMANIAN (<i>Alternate</i>)	
SHRI I. N. MURTY	Department of Explosives, Nagpur
SHRI CHARANJIT LAL (<i>Alternate</i>)	
DR A. G. NAIK-KURADE	All India Food Preservers' Association, New Delhi
SHRI Y. K. KAPOOR (<i>Alternate</i>)	
SHRI P. V. NARAYANAN	Indian Institute of Packaging, Bombay
SHRI K. B. GUPTA (<i>Alternate</i>)	
SHRI A. R. VIJAYENDRA RAO	Central Food Technological Research Institute, (CSIR); Mysore
SHRI HARSHAD F. SHAH	The Indian Paint Association, Calcutta
SHRI D. B. CHATTERJEE (<i>Alternate</i>)	
SHRI S. SINGARAVELU	Tri-Sure India Limited, Bombay
SHRI S. P. BANERJEA (<i>Alternate</i>)	
SHRI S. C. SINGHAL	Vanaspati Manufacturers Association of India, Bombay
SHRI RAJ KAPILA (<i>Alternate</i>)	
SHRI D. SRIDHARAN	Directorate of Sugar & Vanaspati (Ministry of Agriculture and Irrigation), Department of Food, New Delhi
DR M. R. SUBBARAM (<i>Alternate</i>)	
SHRI J. S. UPPAL	Directorate of Marketing & Inspection (Ministry of Agriculture & Irrigation), Department of Rural Development, Faridabad
SHRI S. JAYARAMAN (<i>Alternate</i>)	
SHRI P. S. DAS, Director (MCPD)	Director General, ISI (<i>Ex-officio Member</i>)
<i>Secretary</i>	
SHRI A. R. GULATI Assistant Director (MCPD), ISI	

Metal Closures for Glass Containers Subcommittee, MCPD 12:7

<i>Convener</i>	
SHRI J. K. KHOSLA	The Metal Box Company of India Ltd, Calcutta
<i>Members</i>	
SHRI K. R. NARASIMHAN (<i>Alternate to</i> Shri J. K. Khosla)	
SHRI P. C. AMIN	Alembic Chemical Works Co Ltd, Vadodara
SHRI J. C. PANCHAL (<i>Alternate</i>)	
SHRI S. M. BHAGAT	Zenith Tin Works Limited, Bombay
SHRI P. D. KATRAK (<i>Alternate</i>)	
SHRI P. K. GUPTA	Containers and Closures Ltd, Bombay
SHRI M. K. CHATTERJEE (<i>Alternate</i>)	
SHRI G. S. KADDBET	Poysha Industrial Company Limited, Bombay
LT-COL KAPIL MOHAN	All India Distillers' Association, New Delhi

(Continued on page 8)

Indian Standard

SPECIFICATION FOR ROLL SEAL PILFERPROOF CLOSURES

0. FOREWORD

0.1 This Indian Standard was adopted by the Indian Standards Institution on 28 February 1977, after the draft finalized by the Metal Containers Sectional Committee had been approved by the Marine, Cargo Movement and Packaging Division Council.

0.2 Pilferproof closures are intended to provide to the contents in a container protection against substitution, adulteration or pilfering. Once the pilferproof cap is fixed on the package, it is ordinarily not possible to tamper with the contents of the package without destroying the special device in the closure which is intended to provide such protection.

0.3 The roll seal aluminium closure is one of the most extensively used pilferproof closure fitted on the glass bottles, containing products, such as liquor, pharmaceuticals, chemicals, syrups and squashes. These closures have a security ring which breaks away from the cap as soon as it is unscrewed.

0.4 The caps are supplied complete in all respects, except for the threads in the side. The liner is compressed by top pressure, which is maintained while spinning discs travel round the cap and press its threads into shape using the glass thread as a former.

0.5 For the purpose of deciding whether a particular requirement of this standard is complied with, the final value, observed or calculated, expressing the result of a test or analysis, shall be rounded off in accordance with IS:2-1960*. The number of significant places retained in the rounded off value should be the same as that of the specified value in this standard.

1. SCOPE

1.1 This standard prescribes the requirements for roll seal pilferproof closures suitable for glass containers with neck finish according to Table 3 of IS:7511-1975†.

*Rules for rounding off numerical values (*revised*).

†Summary sheet on glass container neck finishes.

2. TERMINOLOGY

2.1 For the purpose of this standard, the definitions given in IS:1394-1973* shall apply.

3. REQUIREMENTS

3.1 Dimensions — The roll seal pilferproof closures shall have the dimensions and tolerances as specified in Table 1.

3.2 Material

3.2.1 The shell shall be manufactured from aluminium sheet of thickness 0.23 ± 0.02 mm conforming to 19000 or 19500 of IS:737-197 annealed condition. Aluminium sheet of higher nominal thickness may be used if required by the purchaser.

3.2.2 Wad — The wad may be manufactured from pulp board, faced pulp board cork, faced cork, rubber or any other suitable material. The wad thickness shall be such as to provide effective sealing. The wad diameter shall be such that it is retained by the bead on the shell when assembled. The wad or wad facing shall be compatible with the product packed and shall be non-toxic when used for containers for packing food products.

3.3 Manufacture

3.3.1 Finish — The shell shall be in new and clean condition and shall be reasonably free from all foreign matter. It may be given an internal protective coating and an external protective/decorative coating.

3.3.2 The skirt of the shell shall be so manufactured (usually by perforation) that on opening the assembled closure, a ring of metal shall part from the main body of the shell.

3.4 Assembly

3.4.1 The wad shall be assembled to the shell and retained by a bead.

3.4.2 The shell with the wad shall be assembled on to the container neck by roll sealing and crimping.

4. SAMPLING AND TESTING

4.1 The samples of pilferproof closures and glass containers sealed with pilferproof closures for carrying out the tests specified in 4.2 and 4.3 respectively, shall be drawn in accordance with IS : 6941-1973‡.

4.2 The samples of the pilferproof closures shall be tested for dimensions given in Table 1.

*Glossary of terms relating to metal containers trade (*second revision*).


†Specification for wrought aluminium and aluminium alloys, sheet and strip (for general engineering purposes) (*second revision*).

‡Methods of sampling metal closures.

TABLE 1 DIMENSIONS FOR ROLL SEAL PILFERPROOF CLOSURES

(Clauses 3.1 and 4.2)

All dimensions in millimetres.



SL. No.	TYPE	NOM SIZE	A		B		C	
			Max (4)	Min (5)	Max (6)	Min (7)	Max (8)	Min (9)
(1)	(2)	(3)						
i)	Standard	22	22.5	22.1	22.9	22.5	15.5	14.7
ii)		25	25.5	25.1	26.1	25.7	16.9	16.1
iii)		28	28.4	28.0	28.8	28.4	18.3	17.5
iv)		31.5	31.5	31.1	31.9	31.5	18.3	17.5
v)		53	53.8	53.3	54.3	53.8	18.7	17.9
vi)		70	70.5	70.0	71.0	70.5	18.1	17.3
vii)	Shallow	38	38.5	38.0	39.0	38.5	16.5	15.7
viii)		46	46.2	45.7	46.7	46.2	16.6	15.8
ix)	Deep	31.5	31.5	31.1	31.9	31.5	24.3	23.5
x)	Extra deep	30	29.6	29.2	30.0	29.6	34.9	34.1

4.3 The samples of the glass containers sealed with the pilferproof closures shall be tested with the help of the torque tester shown in Fig. 1. The maximum opening torque for efficiently sealed closures shall be in accordance with Table 2.




FIG. 1 TORQUE TESTER

5. MARKING

5.1 The manufacturer's name, initials or recognised trade-mark shall be clearly and indelibly marked on the shell, if so required by the purchaser.

**TABLE 2 OPENING TORQUE VALUES FOR
PILFERPROOF CLOSURES**

(Clause 4.3)

SIZE OF CLOSURE	TYPE	MAXIMUM OPENING TORQUE
(1)	(2)	(3)
mm		N.cm
22	Standard	110
25		125
28		140
31.5		160
53		250
70		290
38	Shallow	185
46		230
31.5	Deep	160
30	Extra deep	150

5.1.1 The closures may also be marked with the Standard Mark.

5.2 The use of the Standard Mark is governed by the provisions of *Bureau of Indian Standards Act, 1986* and the Rules and Regulations made thereunder. The details of conditions under which the licence for the use of Standard Mark may be granted to manufacturers or producers may be obtained from the Bureau of Indian Standards.

(Continued from page 2)

<i>Members</i>	<i>Representing</i>
SHRI K. R. MALHOTRA	India Foils Ltd, Calcutta
SHRI A. RAY (<i>Alternate</i>)	
MAJ S. K. MISRA	Ministry of Defence (DGI)
SHRI V. K. BAJPAI (<i>Alternate</i>)	
SHRI C. K. SOMANY	Hindustan National Glass & Industries Limited, Calcutta
SHRI R. K. GUPTA (<i>Alternate</i>)	
SHRI V. S. SUNDARAM	Glaxo Laboratories (India) Limited, Bombay
SHRI H. K. UPADHYAYA	Larsen & Toubro Limited, Bombay
SHRI J. S. UPPAL	Directorate of Marketing & Inspection (Ministry of Agriculture & Irrigation), Department of Rural Development, Faridabad
SHRI S. JAYARAMAN (<i>Alternate</i>)	
SHRI YASEEN A. VAZIRALLI	Vazir Glass Works Limited, Bombay
SHRI S. D. MARKETKAR (<i>Alternate</i>)	

BUREAU OF INDIAN STANDARDS

Headquarters:

Manak Bhavan, 9 Bahadur Shah Zafar Marg, NEW DELHI 110002

Telephones: 323 0131, 323 3375, 323 9402

Fax : 91 11 3234062, 91 11 3239399, 91 11 3239382

Telegrams : Manaksanstha
(Common to all Offices)

Central Laboratory:

Plot No. 20/9, Site IV, Sahibabad Industrial Area, SAHIBABAD 201010

Telephone
8-77 00 32

Regional Offices:

Central : Manak Bhavan, 9 Bahadur Shah Zafar Marg, NEW DELHI 110002 323 76 17

*Eastern : 1/14 CIT Scheme VII M, V.I.P. Road, Maniktola, CALCUTTA 700054 337 86 62

Northern : SCO 335-336, Sector 34-A, CHANDIGARH 160022 60 38 43

Southern : C.I.T. Campus, IV Cross Road, CHENNAI 600113 235 23 15

†Western : Manakalaya, E9 Behind Marol Telephone Exchange, Andheri (East),
MUMBAI 400093 832 92 95

Branch Offices:

'Pushpak', Nurmohamed Shaikh Marg, Khanpur, AHMEDABAD 380001 550 13 48

‡Peenya Industrial Area, 1st Stage, Bangalore - Turnkur Road,
BANGALORE 560058 839 49 55

Gangotri Complex, 5th Floor, Bhadbhada Road, T. T. Nagar, BHOPAL 462003 55 40 21

Plot No. 62-63, Unit VI, Ganga Nagar, BHUBANESHWAR 751001 40 36 27

Kalaikathir Buildings, 670 Avinashi Road, COIMBATORE 641037 21 01 41

Plot No. 43, Sector 16 A, Mathura Road, FARIDABAD 121001 8-28 88 01

Savitri Complex, 116 G. T. Road, GHAZIABAD 201001 8-71 19 96

53/5 Ward No. 29, R. G. Barua Road, 5th By-lane, GUWAHATI 781003 54 11 37

5-8-58C, L. N. Gupta Marg, Nampally Station Road, HYDERABAD 500001 20 10 83

E-52, Chitaranjan Marg, C-Scheme, JAIPUR 302001 37 29 25

117/418 B, Sarvodaya Nagar, KANPUR 208005 21 68 76

Seth Bhawan, 2nd Floor, Behind Leela Cinema, Naval Kishore Road,
LUCKNOW 226001 23 89 23

Patliputra Industrial Estate, PATNA 800013 26 23 05

T. C. No. 14/1421, University P. O. Palayam,
THIRUVANANTHAPURAM 695034 6 21 17

NIT Building, Second Floor, Gokulpat Market, NAGPUR 440010 52 51 71

Institution of Engineers (India) Building, 1332 Shivaji Nagar, PUNE 411005 32 36 35

*Sales Office is at 5 Chowringhee Approach, P. O. Princep Street,
CALCUTTA 700072 27 10 85

†Sales Office is at Novelty Chambers, Grant Road, MUMBAI 400007 309 65 28

‡Sales Office is at 'F' Block, Unity Building, Narashimaraja Square,
BANGALORE 560002 222 39 71

AMENDMENT NO. 1 MARCH 1979
TO
IS : 8393 - 1977 SPECIFICATION FOR ROLL
SEAL PILFERPROOF CLOSURES

Alteration

(*Page 4, clause 3.2.1*) — Substitute the following for the existing clause:

'3.2.1 The shell shall be manufactured from aluminium sheet conforming to designation 40800 or 31000 of IS : 737 - 1974† and shall be in H₂ or H₃ hardness. The thickness of the various sizes of aluminium sheet shall be as under:

For closures up to and including 28 mm size	0.20 ± 0.02 mm
--	--------------------

For closures above 28 mm size	0.23 ± 0.02 mm
-------------------------------	--------------------

Aluminium sheets of higher nominal thickness may be used if required by the purchaser.'

(MCPD 12)